



General Specifications

- Aluminium (silver anodized) enclosure
- Registered trammed perspex slab with easy change sign pad
- Single and/or double sided available
- Designed for indoor use
- Long life LED technology (>100,000 hours)
- Recessed, wall bracket or ceiling bracket, suspended
- Central monitoring & Self-Test available with DALI models
- Manufactured to comply with EN60598-2-22
- ENEC Certification by TÜV-Rheinland


Technical Specifications

System Mode	: Maintained & Non-Maintained operating modes for standard models, switchable maintained (M/NM together) operating modes for DALI models
Input Voltage	: 230V, 50/60Hz 24V or 230V AC/DC (centrally powered)
Light Source	: 10 x Led (60 Lumen), 20 x Led (120 Lumen) for DALI models
Charging Indicator	: Green LED
Fault Indicator	: Red LED (DALI & Self-Test models only)
Battery	: High temp Ni-Cd battery block, DALI models high temp Ni-MH battery block
Emergency Duration	: 3 hours
Insulation Class	: Class I
Protection Class	: IP30
Temperature	: 0 - 35°C
Enclosure / Color	: Aluminium / Silver
Side Covers / Color	: Polycarbonate / Gray
Viewing Distance	: 24m, 30m (DALI models)

Ordering Details

Product Code	Model	Operating Mode	Mounting Details	Light Source	Duration
UTLZNC-M310	Standard	M Maintained	Chain	10xLED (60 Lumen)	3 hours
UTLBRK-M310			Bracket		
UTLANK-M310		Recessed			
UTLZNC-NM310		Chain			
UTLBRK-NM310		Bracket			
UTLANK-NM310	NM Non-Maintained	Recessed			
UTLZNC-M310-ST		Chain			
UTLBRK-M310-ST	Self-Test	M Maintained	Chain	20xLED (120 Lumen)	
UTLANK-M310-ST			Bracket		
UTLZNC-SM320-DALI		SM Switchable Maintained (M/NM together)	Recessed		
UTLBRK-SM320-DALI	Chain				
UTLANK-SM320-DALI	DALI		Bracket	10xLED (60 Lumen)	Centrally Powered
UTLZNC-1024			Recessed		
UTLBRK-1024		24V AC/DC	Chain		
UTLANK-1024			Bracket		
UTLZNC-10230	Central	230V AC/DC	Recessed		
UTLBRK-10230			Chain		
UTLANK-10230		Bracket			
PLX-UTL-T1		Trammed Perspex Slab with Easy Change Sign Pad, Single Sided			
PLX-UTL-T2		Trammed Perspex Slab with Easy Change Sign Pad, Double Sided			
PET-UTL		Sign pad (spare part)			
PET-UTL-WHT		White pad (spare part)			
PLX-UTL-DALI-T1		Trammed Perspex Slab with Easy Change Sign Pad, Single Sided			
PLX-UTL-DALI-T2		Trammed Perspex Slab with Easy Change Sign Pad, Double Sided			
PET-UTL-DALI		Sign pad (spare part)			
PET-UTL-DALI-WHT		White pad (spare part)			

Dimensions



Meer info ?

Project Zero

Windhoek 29 - 8790 Waregem

T +32 56 711 501

E sales@project-zero.be

www.PROJECT-ZERO.be