

SALINA



Colours	☐ ■
Housing	Aluminium
Inner ring colours	White, Black, Gold
Fixture type	Pendant
Module	Citizen LED
Driver	TRIAC-dimmable driver incorporated in ceiling cap
Light Output module	600lm
CCT	2700K
CRI	>90Ra
Beam angles	50°
LED modules	Standard
Dimming Options	TRIAC (standard)
Options	3-Circuit Track Adapter
Expected Lifetime	40.000h (L70/B30)
Suspension length	145 cm
Power factor	> 0.9
UGR	< 19
Colour consistency	3 SDCM
Warranty	3 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
550 grams	9 x 7 x 58 cm	10

Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Citizen LED	600lm	7W	85	927	>90						



LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.