


Monocrystalline Photovoltaic Module »



MEPV 120 HALF-CUT

BLACK » 340Wp



QUALITY »



120 cells
Half-Cut monocrystalline



MBB technology
Better light absorption



Fire resistance
Maximum protection



+5W
Positive power tolerance



Avoid losses
Better shading tolerance



Optimal performance
Power and efficiency



1997 to 2022
25TH
ANNIVERSARY

*** EUROPEAN QUALITY

PREMIUM PARTNER WARRANTY »

20 YEARS PRODUCT WARRANTY

25 YEARS PERFORMANCE WARRANTY
Linear Warranty

CERTIFICATES »



TECHNICAL FEATURES »

Eurener_MEPV 120_HALF-CUT_340Wp_2022EN

FRAME

Black anodized aluminium

Robust and resistant to corrosion

CONNECTION BOX AND PROTECTIONS

Sealed, robust and wide for heat dissipation

IP67/IP68 according to IEC 60529

Diodes by-pass built-in (3/6)

Connector MC4 compatible

Application Class A. Safety Class II

Cables 1000 mm ($\pm 20\%$) length and 4 mm² section

FRONTAL

3,2 mm thick tempered glass with high strength and ARC

Textured, extra-clear with low iron content



Frontal load (snow) 5.400 Pa | Back load (wind) 2.400 Pa

SOLAR CELLS

120 [2x(10x6)] cells monocrystalline silicon

WEIGHT, DIMENSIONS AND PACKAGING

18 Kg | 1684 x 1002 x 35 mm ($\pm 1\%$) | Pack: 858 pcs-truck



ELECTRIC DATA »

BLACK	MEPV 340
STC: 1000 W/m ² , module temperature 25°C, AM 1,5	
Nominal power. P _{mpp}	340 Wp
Tolerance. P _{mpp}	0 / +5 W
Area of the module	1,68 m ²
Module efficiency	20,16 %
I _{sc}	10,26 A
V _{oc}	43,00 V
I _{mpp}	9,75 A
V _{mpp}	34,90 V
NOCT: 800 W/m ² , ambient temperature 20°C, AM 1,5	
Nominal power. P _{mpp}	257,52 W
I _{sc}	7,68 A
V _{oc}	40,60 V
I _{mpp}	7,78 A
V _{mpp}	33,10 V
Operating parameters. Temperature coefficients	
Maximum voltage	1000 - 1500 V
Maximum series fuse rating. I _r	20 A
α I _{sc}	0,04 % / °C
β V _{oc}	- 0,26 % / °C
γ P _{max}	- 0,36 % / °C
Temperature range	- 40°C ~ + 85 °C
NOCT	41 $\pm$ 3 °C

NOTE: Read the instruction manual of this product and follow the indications STC. Values are valid for: 1000W/m², AM 1,5 and cells temperature of 25°C. Measurement tolerance $\pm 3\%$ (AAA Solar simulation -IEC 60.904-9-). All the information of this brochure may be amended without notice by Eurener. Eurener_MEPV 120_HALF-CUT_340Wp_EN_MAR2022

www.eurenergroupp.com

contact@eurenerworld.com
+34 960 045 515

Calle Colón, 1-23
46004 Valencia. Spain

www.project-zero.be

sales@project-zero.be
+32 (0)56 71 15 01

Windhoek 29
8790 Waregem. Belgium

PROJECT
ZERO
one stop energy shop